



- Optional Beam Angle
- Clear or Color glass optional
- Color Temperature: 2800k
- UV STOP

Model



Model	V	W	GU5.3	°	cd	t[h]	Ø Gmax [mm]	lmax [mm]
MR1612V 20W ESX	12V	20W	GU5.3	12	3500	2000	50	45
MR1612V 20W BBF	12V	20W	GU5.3	24	1500	2000	50	45
MR16 12V 20W BAB	12V	20W	GU5.3	38	600	2000	50	45
MR16 12V 35W FMT	12V	35W	GU5.3	12	6500	2000	50	45
MR16 12V 35W FMY	12V	35W	GU5.3	24	3500	2000	50	45
MR16 12V 35W FMW	12V	35W	GU5.3	38	750	2000	50	45
MR16 12V 50W EXT	12V	50W	GU5.3	12	9500	2000	50	45
MR16 12V 50W EXZ	12V	50W	GU5.3	24	3500	2000	50	45
MR16 12V 50W EXN	12V	50W	GU5.3	38	1800	2000	50	45
MR16 12V 50W FNV	12V	50W	GU5.3	60	800	2000	50	45
MR16 12V 35W Square	12V	35W	GU5.3			2000		
MR16 12V 50W Hexagon	12V	50W	GU5.3			2000		
MR16 12V 35W Square	12V	35W	GU5.3			2000		
MR16 12V 50W Hexagon	12V	50W	GU5.3			2000		